

PERFORMANCE DATA

SIZES: TEXTLINE FABRICATED FITTINGS ARE AVAILABLE IN SIZES FROM 1" THROUGH 24" PIPE IN SCHEDULES 7, 10 AND 40.

QUALITY ASSURANCE: TEXTLINE FITTINGS ARE MANUFACTURED TO STRICT QUALITY STANDARDS. FITTINGS ARE TESTED FOR LEAKAGE, GROOVE AND CENTER TO END DIMENSIONS.

AMERICAN MADE: TEXTLINE FITTINGS ARE MANUFACTURED IN THE UNITED STATES FROM DOMESTICALLY MANUFACTURED MATERIAL.

COATINGS: TEXTLINE FABRICATED FITTINGS ARE BLASTED TO BARE MILL AND COATED BOTH INSIDE AND OUTSIDE WITH STANDARD ORANGE COATING OR HOT DIPPED GALVANIZED.

APPROVALS: TEXTLINE FITTINGS ARE MANUFACTURED TO THE SPECIFICATIONS AND APPROVED BY FACTORY MUTUAL, UNDERWRITER'S LABORATORY, UNDERWRITER'S LABORATORY OF CANADA AND THE CITY OF LOS ANGELES.

SPECIFICATIONS: TEXTLINE FABRICATED FITTINGS HAVE BEEN TESTED AND LISTED OR APPROVED BY UL AND FM FOR THE PRESSURE RATINGS LISTED IN THE TABLE BELOW.

PIPE SIZE	STAINLESS			
	SCH 7	SCH 10	SCH 40	SCH 40
1 1/4"	300 PSI	300 PSI	300 PSI	300 PSI
1 1/2"	300 PSI	300 PSI	300 PSI	300 PSI
2"	300 PSI	300 PSI	300 PSI	300 PSI
2 1/2"	300 PSI	300 PSI	300 PSI	300 PSI
3"	300 PSI	300 PSI	300 PSI	300 PSI
3 1/2"	300 PSI	300 PSI	300 PSI	300 PSI
4"	300 PSI	300 PSI	300 PSI	300 PSI
5"	N/A	300 PSI	300 PSI	
6"	200 PSI	300 PSI	300 PSI	
8"		300 PSI	300 PSI	
10"		250 PSI	250 PSI	
12"		300 PSI	300 PSI	
12" TEE UL		250 PSI	250 PSI	
12" TEE FM		200 PSI	200 PSI	
12" CROSS UL		200 PSI	200 PSI	
SPIGOT ASSM		175 PSI	N/A	
FLOOR ASSM		175 PSI	175 PSI	

FLOW DATA FOR SEGMENTALLY WELDED ELLS

	EQUIVALENT FEET	K FACTOR
2" 90 ELL	5	0.69
2 1/2" 90 ELL	6	0.64
3" 90 ELL	7	0.63
4" 90 ELL	10	0.75
6" 90 ELL	14	0.62
8" 90 ELL	18	0.62